

CERTIFICATE

544202

SP decides on certification of the product described according to the Swedish Civil Contingencies Agency status MSBFS 2009:5

Large packaging for dangerous goods

With specifications as specified on page 2 in this certificate.

Holder

Swede Rehandling System AB

Box 108, 651 04 Karlstad.

Manufacturer

Dolay, Dvir-Lahay Plastic Products, Israel. According to agreement 400-90-0504 Appendix 1

Marking

Each product, manufactured in accordance with Certification Rules SPCR 059, and which is subjected to manufacturing inspection according to Agreement No. 400-90-0504, may be marked as follows:



50H/Y/YR/S/SP-54 42 02-ID/1283/KG

where "YR" is to be replaced by the month and last two digits of the year of manufacture, where "ID" is to be replaced by any identification as decided by the manufacturer and where "KG" is to be replaced by the maximum gross weight according to the table above. The container shall also bear an additional marking: Maximum permitted stacking load in kg.

Regulations supporting the certification

- ADR, European Agreement concerning the International Carriage of Dangerous Goods by Road.
- RID, International Regulations on the Transport of Dangerous Goods by Rail.
- IMDG, International Maritime Dangerous Goods Code, for sea transport.
- UN Recommendations on the Transport of Dangerous Goods.

Validity

This certificate is valid until no longer than 30 June 2022.

Lennart Aronsson

Daniel Andersson

 $This is a translation from the Swedish \ original \ document. \ In \ the \ event \ of \ any \ dispute \ as \ to \ its \ content, \ the \ Swedish \ text \ shall \ take \ precedence.$

Certificate No. 544202 | 2017-10-30

RISE Research Institutes of Sweden AB | Certification Box 857, SE-501 15 Borås, Sweden Phone: +46 10-516 50 00 certifiering@ri.se| www.ri.se







CERTIFICATE

Basis for certification

Report	Date	Issued by	Scope
PX12764	30th August 2011	SP	Type testing
PX21806	7 March 2012	SP	Technical evaluation

Product

Large packaging of rigid plastics, 50H, designed for bottom lift with four sides of entry. Material: HDPE structural form.

Designation	External dimensions	Tare weight	Maximum gross
	(L×W×H)		weight
1000 solid SH - 1000	1200 × 1000 × 1000 mm	52.5 kg	700 kg
1000 solid – standard	1200 × 1000 × 740 mm	45.4 kg	496 kg
800 solid – standard	1200 × 800 × 740 mm	38.0 kg	386 kg

Substance and transport limitations

In addition to the conditions stated in the applicable regulations the following limitations apply for the filling substance:

Permitted type of contents

Articles including aerosols. The content may not adversely affect the packaging materials. Permitted packing groups
II and III